

Wind sensor Standard

| Specification | Order No. | Packing unit | PS | EAN |
|---------------|-----------|--------------|----|---------------|
| | 0913 00 | 1 | 06 | 4010337913009 |

Features

- The wind sensor enables e.g. blinds to be raised depending on the wind strength. In this way, sensitive blind slats can be protected from increasing wind.
- Recording and evaluating wind speeds.
- 8 adjustable wind strengths.
- Wind alarm is triggered 15 seconds after the set wind strength threshold is exceeded.
- Test run for function testing.
- Evaluation unit: Surface-mounted device for indoor installation in dry rooms.
- Wind transmitter: Device for outdoor installation.

Technical data

| | |
|---|---|
| Wind transmitter | |
| - Material of the transmitter and cup anemometer: | Plastic (ABS), black |
| - Cup diameter: | Dia. 134, H 160 |
| - Ambient temperature: | -20 °C to +55 °C |
| - Connection cable: | JY-ST-Y 2 x 0.6 mm ² , length 3 m (can be extended to max. 50 m) |
| - Protection class: | IP55 |
| Evaluation unit | |
| - Wind warning range: | 3.3 to 24.5 m/s, can be set to one of 8 levels |
| - Switching contact: | Relay with zero-voltage NO contact |
| - Load capacity: | max. 2 A |
| - Operating voltage: | AC 230?V |
| - Protection class: | IP20 |
| Dimensions | |
| - W x H x D: | 110 mm x 99 mm x 38 mm |

Scope of supply

- Mounting bracket included with delivery.
-