GIRA Data sheet

© Copyright by Gira Giersiepen GmbH & Co. KG All rights reserved

www.gira.com

Pushbutton sensor 4.95, 24 V 1-gang

| Specification | Order No. | Packing unit | PS | EAN |
|---------------|-----------|--------------|----|---------------|
| white | 5051 003 | 1 | 02 | 4010337074960 |
| anthracite | 5051 028 | 1 | 02 | 4010337074977 |

Features

- Pushbutton sensor 4.95 for connection to 24 V control systems.
- Pushbutton sensor 4.95 must be completed with rocker sets to be ordered separately. The operating surfaces of the rocker sets are made of high-quality three-millimetre thick real material such as glass, stainless steel or aluminium.
- Two white status LEDs per rocker.
- Measurement of the room temperature with integrated temperature sensor (PT1000).

Technical data

Button

- Rated voltage: AC/DC 24 V SELV - Current capacity: 20 mA per button

- Output resistance: 088

LED

- Rated voltage: DC 24 V SELV - Current consumption: approx. 1 mA per LED

PT1000, class B Temperature sensor:

Protection class: Ш

Installation depth: 16 mm

-5 °C to +45 °C Ambient temperature:

GIRA Data sheet

catalogue.gira.com

© Copyright by Gira Giersiepen GmbH & Co. KG All rights reserved

www.gira.com

Notes

- Suitable for SELV circuits only.
 Professional inscription by the Gira inscription servicewww.marking.gira.com.

Scope of supply

- The pushbutton sensor is delivered with a program-neutral start-up rocker. The suitable rocker set for the switch range must be ordered separately.