

Weather sensor with weather control unit for KNX

| Specification | Order No. | Packing unit | PS | EAN |
|---------------|-----------|--------------|----|---------------|
| | 5146 00 | 1 | 06 | 4010337124405 |

Features

- The components of the weather station consisting of a weather sensor and a weather control unit cannot be used individually.
- The weather sensor has the following sensors:
 - Brightness from three directions (at 90° intervals to each other, compass directions: east, south, west)
 - Temperature
 - Wind speed
 - Precipitation sensor, with integrated heating
- The weather sensor sends the sensor values to the weather control unit, which evaluates the sensor information and sends it to the KNX bus.
- The weather sensor can communicate with up to 20 weather control units (5147 00).
- 10 sensor channels for wind, precipitation, temperature and brightness. Logical AND/OR links can be created within the sensor channels to evaluate multiple sensor values together.
- Evaluation delay for all sensors to ensure reliable functionality.
- 8 sun protection channels for 8 facades with automatic sun protection function incl. evaluation delay to ensure a reliable sun protection function.
- 2 objects for external brightness sensors.
- Pre-defined day/night object for switchover between day/night mode incl. separate activation/deactivation function via the communication object.
- Communication object that provides information about any communication problems between the weather control unit and the weather sensor.

Technical data

Weather sensor

- Operating voltage of ext. power supply: DC 18 – 34 V
- Internal consumption: max. 5 W
- Connection between weather sensor and weather control unit: 0.6 to 0.8 mm (bus line e.g. J-Y(St)Y 2 x 2 x 0.8)
- Connection type: Spring plug-in terminal and connection terminal
- Mounting type: Wall or mast mounting
- Protection class: IP44
- Protection class: III
- Rated surge voltage: 0.8 kV
- Ambient temperature: -20 °C to +55 °C
- Wind measuring range: 2 to 30 m/s
- Brightness measuring range: 1 to 100,000 lux

| | |
|--|--|
| - Temperature measuring range: | -30 °C to +60 °C |
| - Dimensions in mm: | W 121 H 105 D 227 |
| Weather control unit | |
| - KNX medium: | TP256 |
| - KNX rated voltage: | DC 21 to 32 V SELV |
| - Internal consumption: | max. 0.5 W |
| - KNX connection: | 0.6 to 0.8 mm (bus line e.g. J-Y(St)Y 2 x 2 x 0.8) |
| - Maximum cable length between weather sensor and weather control unit: | 1,000 m |
| - Protection class: | IP20 |
| - Protection class: | III |
| - Rated surge voltage: | 0.8 kV |
| - Number of weather control units that can be connected to a weather sensor: | 20 |
| - Ambient temperature: | -5 °C to +45 °C |

Notes

- KNX Data Secure compatible.
 - Prepared for Gira One.
-

Scope of supply

- Connection and junction terminal for KNX included with delivery.
-

Dimensions

| | |
|---------------------|---|
| Modular width (MW): | 3 |
|---------------------|---|
