catalogue.gira.com

GIRA Data sheet

© Copyright by Gira Giersiepen GmbH & Co. KG All rights reserved

www.gira.com

Antenna socket insert (SE33ST)

Specification	Order No.	Packing unit	£/piece without VAT	PS	EAN
	0937 00	1/5	31.94	01	4010337937005

Features

- Stub cable outlet with three connections.
- The IEC plug for terrestrial TV is located on the bottom left, the IEC socket for FM (radio) on the bottom right and at the top centre is the F connector for satellite TV (SAT).
- Channel filter for terrestrial and satellite television with high attenuation rate: The SAT signal is filtered in the FM-TV-IEC connections, while the terrestrial FM/TV signal is filtered in the satellite F connection.
- DC feed-through from the SAT connection to the input.
- The internal conductor is connected simply by pressing it, without the need for screws. Internal conductor can thus be removed multiple times.
- Complies with shield class A.

Technical data

UKW frequency band

- Frequency range: 87.5 to 108 MHz

- Decoupling: > 10 dB

UKW frequency band: 4 dB

TV frequency band

Frequency range:
Decoupling:
Attenuation: TV plug:
125 to 862 MHz
10 dB
4 dB

SAT frequency band

- Frequency range: 950 to 2400 MHz

Decoupling: > 20 dBAttenuation: SAT plug: 1.5 dB

Installation depth: 36 mm

GIRA Data sheet

catalogue.gira.com

© Copyright by Gira Giersiepen GmbH & Co. KG All rights reserved

www.gira.com

N	nto.	

- For screw attachment only.