GIRA Data sheet

catalogue.gira.com

© Copyright by Gira Giersiepen GmbH & Co. KG All rights reserved

www.gira.com

Wireless module for Dual Q smoke alarm device

Specification	Order No.	Packing unit	£/piece without VAT	PS	EAN
	2347 00	1	60.02	03	4010337016632

Features

- Wireless module for the wireless connection of Dual Q smoke alarm devices.
- Downwards-compatible, therefore it can also be used for smoke alarm device Dual/VdS.

Technical data

Wireless frequency: 433.42 MHz

Range (free field): approx. 100 m

Power supply: from the battery of the wireless module

Battery

- Type: CR 2/3 AA lithium

- Capacity: 3 V - UN no.: 3091

Notes

- If one smoke alarm device detects a fire, all the assigned smoke alarm devices sound the alarm.
- The wireless module is plugged into the interface of the Dual smoke alarm device. The networking terminals of the smoke alarm device can continue to be used when the module is attached. This allows combined lines to be set up (wired or via radio).
- Due to the compatibility with the wireless bus system, alarm messages can be used to actuate the wireless actuators. This can be used to switch the light or raise the blinds, for example, in the event of an alarm.
- From index levell02or higher, the wireless module for the Dual smoke alarm device is compatible with the wireless diagnostic tool(2333 00).
- The battery cannotbe sourced from Gira as a spare part.

GIRA Data sheet

catalogue.gira.com

© Copyright by Gira Giersiepen GmbH & Co. KG All rights reserved

www.gira.com

Scope of supply	Scope	of	sup	ply
-----------------	-------	----	-----	-----

- Battery is included with delivery.